

KLEMBUSWIELEN - DUPLEX

Voor rollenketting 08B-2

Vlgs. Din 8187

1/2" x 5/16"

Tanden aantal	Klembus	Naaf afmeting		Steek cirkel	Kop cirkel	Artikel code
Z		Dm mm	A mm	Dp mm	De mm	
15	1008	46	22	61,80	66,50	KBW08B-2 15T-H
16	1108	46	22	65,10	69,90	KBW08B-2 16T-H
17	1210	56	25	69,11	74,50	KBW08B-2 17T-H
18	1210	60	25	73,14	78,00	KBW08B-2 18T-H
19	1210	62	25	77,15	82,50	KBW08B-2 19T-H
20	1210	62	25	81,19	86,00	KBW08B-2 20T-H
21	1610	70	25	85,21	90,60	KBW08B-2 21T-H
22	1610	70	25	89,24	94,10	KBW08B-2 22T-H
23	1610	79	25	93,26	98,70	KBW08B-2 23T-H
24	1610	79	25	97,29	102,10	KBW08B-2 24T-H
25	2012	87	32	101,32	106,70	KBW08B-2 25T-H
26	2012	87	32	105,36	110,20	KBW08B-2 26T-H
27	2012	87	32	109,40	114,80	KBW08B-2 27T-H
28	2012	87	32	113,42	118,30	KBW08B-2 28T-H
29	2012	87	32	117,44	124,80	KBW08B-2 29T-H
30	2012	87	32	121,49	126,90	KBW08B-2 30T-H
31	2012	87	32	125,51	131,10	KBW08B-2 31T-H
32	2012	87	32	129,53	135,30	KBW08B-2 32T-H
33	2012	87	32	133,55	139,50	KBW08B-2 33T-H
34	2012	87	32	137,57	143,70	KBW08B-2 34T-H
35	2012	87	32	141,59	147,90	KBW08B-2 35T-H
36	2012	87	32	145,61	152,10	KBW08B-2 36T-H
37	2012	87	32	149,63	156,30	KBW08B-2 37T-H
38	2012	100	32	153,79	159,20	KBW08B-2 38T-H
39	2012	100	32	157,81	163,40	KBW08B-2 39T-H
40	2012	100	32	161,83	167,60	KBW08B-2 40T-H
45	2012	100	32	182,07	188,60	KBW08B-2 45T-H
48	2012	100	32	194,13	201,20	KBW08B-2 48T-H
50	2012	100	32	202,17	209,60	KBW08B-2 50T-H
57	2012	111	32	230,54	237,10	KBW08B-2 57T-H
60	2012	111	32	242,60	249,70	KBW08B-2 60T-H
76	2012	111	32	307,32	313,90	KBW08B-2 76T-H
95	2012	111	32	384,11	390,70	KBW08B-2 95T-H
114	2517	111	44	460,90	467,40	KBW08B-2 114T-H

Ook afwijkende tandenaantallen op voorraad, specificaties op aanvraag.

Steek	P	= 12,70 mm
Binnenbreedte	E	= 7,75 mm
Roldiameter	D3	= 8,51mm
Tandbreedte	b1	= 7,00 mm
	B2	= 20,00 mm

